

ATLANTIC PERISTALTIC PUMP

AT 50



The AT 50 is a well-designed, compact, electric driven peristaltic pump. It is simple to operate, easy to clean and extremely light to move around the job site. The peristaltic pumping technology conveys the material by “waving - moving - contractions” without squeezing or damaging it.

ATLANTIC PERISTALTIC PUMP - SPECIFICATIONS

Model	AT 50
Machine Type	Electric Peristaltic Pump
Pump Capacity	0 - 8.5 litre/min
Max. Pressure	12 bar
Max. Grain Size	2 mm
Power Supply	1 Phase Electric Motor 0.55 kW, 230 V, 50 Hz
Weight	55 kg
Dimensions (L x B x H)	800 x 460 x 890 mm

* All data is based on experience and dependent on the materials used. Machine design and construction are subject to technical modifications and upgrades.


AT 50 - Key Features:

- ✓ Consistent and smooth flow of material.
- ✓ Pump capacity can be regulated.
- ✓ Additional socket for Agitator/ Compressor.
- ✓ Simple to operate, no electronics.
- ✓ No damage to pump, if running idle.
- ✓ Low wear and maintenance costs.
- ✓ Quick and easy cleaning.

AT 50 - Applications:

- ✓ Artificial resin plasters up to 2 mm grain size.
- ✓ Acoustic spray plaster.
- ✓ Solvent resistant materials.
- ✓ Deco pearls / Styr pearls.
- ✓ Mineral sealing sludge.
- ✓ Fire protection.
- ✓ Bitumen coating.

DELIVERING MORE EFFICIENCY, FLEXIBILITY AND POWER



ACE CENTRO ENTERPRISES

P. O. Box 95325, Abu Dhabi - U.A.E.

T : +971 2 6737900

F : +971 2 6737800

E : salesteam@acecentro.com

W : www.acecentro.com

